

## Fluid Structure Interaction Based Investigation on Convergent-Divergent Nozzle and Study of Coating Material

Shridevi S Keralamatti

### ABSTRACT

The aim of this paper is to analyze flow in a rocket nozzle and perform FSI simulation for the thermo-mechanical interaction between fluid and solid structure. The nozzle is most important part of the rocket. The proper design plays a major role in the performance of the nozzle, which is designed aerodynamically while considering NPR values. Nozzle is made with Rhenium and coated with Iridium. High speed flow through Convergent-Divergent nozzle leads to complex loading on surrounding structures. The two different cases are carried out and assist the thermal loading on surrounding structures. Structure Interaction analysis is carried in Star CCM+ by creating three different regions i.e., Fluid, Iridium coating (Solid region of 50  $\mu\text{m}$ ) and Rhenium structure (Solid region of 1mm) and this analysis gives a better understanding of the behavior of the thermo-mechanical interaction between solid to fluid regions.

### Keywords:

Fluid Structure Interaction (FSI); Rocket nozzle; Star CCM+; Rhenium and iridium

### INTRODUCTION

A convergent-divergent nozzle is most important component of the rocket engine and it is a combustion chamber extension [1]. The main role of nozzle is to expand and accelerate the gas. The rocket nozzle is designed to control the direction and it is like tube shaped through which hot gases flow. Nozzles are frequently used to control the rate of flow, flow direction, and the pressure of the stream that emerges from them. Size and shape of nozzle depends on mission of the rocket and its application. Nozzle is used even in the turbojet and ramjet engine. During engine startup and shutdown of the rocket nozzle will operate an over expanded mode where the ambient/operating pressure is greater than the internal pressure acting on nozzle wall [2,3]. In nozzle, the flow first

converges down to the throat or minimum area of nozzle and then it is expanded through the divergent section to the exit.

The nozzle is exposed to high temperature and it should be coated in order to prevent the complex thermal loading on surrounding structures [4]. The coating is made with Iridium hence its capable of manage the thermal loads and at same time, which needs to be lighter in the weight in order to maximize the rocket lift capacity. Nozzle play a vital role in determines operating characteristics of a rocket engine. A computational prediction of nozzle flow parameter is main objective this paper.

### MATERIALS AND METHODS

The rocket nozzle dimension as shown in Table 1 is used for CFD modelling. Figure 1 shows overall Dimension of convergent- divergent nozzle [5-7]. Three regions are created i.e., Fluid, Iridium coating (Solid region of 50  $\mu\text{m}$ ) and Rhenium structure (Solid region of 1 mm). For solid regions (Iridium coating and Rhenium) created two physics and applied respective material [8,9]. Figure 2 shows the region or material nomenclature of Nozzle, which is modelled in Star CCM+. Interface has been created between regions by selecting common surface from each region. Polyhedral and trimmer mesh has generated for one case and conducted the simulation for Nozzle. Wall treatment is taken care into account and generated desired prism layer for the both type of mesh. Results from these two type of mesh are same results. Further simulation has been carried for polyhedral mesh since cell count is lesser than the trimmer mesh. Figure 3 shows the cut- section of polyhedral mesh on convergent-divergent nozzle. Total cell count is around 2 million for polyhedral mesh. Two cases has been conducted,

### RESULTS AND DISCUSSION

3D modeling is done and performed the CFD analysis. The desired number of iterations given and then launched the simulation. Convergence is achieved within the 1500 iteration .Examined Nozzle temperature profile on solid wall .Assisted thermal loading on surrounding structures

Shridevi S Keralamatti

MVJ College of Engineering, Bangalore, shree.sk1991@gmail.com

with Iridium coating. Iridium coating reduce the thermal loading on surrounding structures and prevent from damage. Figures 5-10 are for the case 1.

For case 2, temperature boundary condition has been changed and performed simulation. Similarly, as per case examined Nozzle temperature profile on solid wall .Assisted thermal loading on surrounding structures with Iridium coating.

## CONCLUSIONS

From the CFD (FSI) simulation, we have following conclusions:

1. Coupled fluid structure interaction analysis has been carried out on convergent-divergent nozzles of different operating condition.
2. It is observed that, from the both cases velocity increases when pressure values deceases in the convergent-divergent nozzle. Velocity values are suddenly expanded after throat section.

## REFERENCES

1. Khan AA, Shembharkar TR. Viscous flow analysis in a convergentdivergent nozzle. Proceedings of the International Conference on Aero Space Science and Technology, Bangalore, India. 2008.
2. Baig MAA, Khan SA, Rathakrishnan E. Active control of base pressure in suddenly expanded flow for area ratio 4.84. Int J Eng Sci Technol. 2012;4:1892-1902.
3. Ali A, Neely A, Young J, Blake B, Lim JY. Numerical simulation of fluidic modulation of nozzle thrust. 17<sup>th</sup> Aus-tralasian Fluid Mechanics Conference. 2010.
4. Anderson JS, Williams TJ. Base pressure and noise produced by the abrupt expansion of air in a cylindrical duct. J Mech Eng Sci. 1968;10:262-268.
5. <https://www.scribd.com/doc/316668483/ANSYS-Fluent-Theory-Guide-pdf>.
6. Khan SA, Aabid A. CFD Analysis of CD nozzle and effect of nozzle pressure ratio on pressure and velocity for suddenly expanded flows. Int J Mech Prod Eng Res Dev. 2018;8:1147-1158.
7. Versteeg HK, Sekhara WM. An introduction to computational fluid dynamics. British Library Cataloguing Pub, 4<sup>th</sup> ed. 1996.
8. Wilcox DC. Turbulence modeling for CFD. Second ed. 1998;2:1.
9. Khan SA, Rathakrishnan E. Active control of suddenly expanded flows from overexpanded nozzles. Int J Turbo Jet Eng. 2002;19:119- 126.
10. Khan SA, Rathakrishnan E. Control of suddenly expanded flows with micro-jets. Int J Turbo Jet Eng. 2003;20:63-82.