conferenceseries.com

19th International Congress on

NUTRITION & HEALTH

April 12-14, 2018 | Amsterdam, Netherlands

J Nutr Food Sci 2018, Volume:8 DOI: 10.4172/2155-9600-C1-054

Electromembrane extraction combined with capillary electrophoresis for the determination of organophosphorus in wastewater and food samples

Ehsan Sadeghi

Shahid Beheshti University, Iran

lectromembrane extraction (EME) is a sample preparation technique in pharmaceutical, chemical, clinical and environmental Lanalysis. This technique uses electromigration across artificial liquid membranes for selective extraction of analytes and sample enrichment from complex matrices. This method has many advantages such as simplicity, rapid, low-cost, low LOD, high preconcentration factor and high recovery. In the present work, simultaneous preconcentration and determination of Organophosphorus such as Glyphosate (GLP), Malathion (MAT), Ethion (ETH), Dimethoate (DMT) were studied using EME as a suitable extraction method, followed with capillary electrophoresis (CE) using ultraviolet (UV) detection as separation technique. The Organophosphorus were extracted from 4 ml sample solutions, through a supported liquid membrane (SLM) consisting 2-nitrophenyloctylether (NPOE) impregnated in the walls of a polypropylene hollow fiber, and into a 20µL acidic aqueous acceptor solution resent inside the lumen of the hollow fiber with a potential difference applied over the SLM. The variables of interest, such as chemical composition of the organic liquid membrane, stirring speed, extraction time and voltage, pH of donor and acceptor phases and salt effect in the EME process were investigated and optimized. Under optimal conditions NPOE as SLM, stirring rate of 1000rpm, 200V potential differences, 20min as the extraction time, acceptor phase HCl (pH 1.0) and donor phase HCl (pH 1.5). After the microextraction process, the extracts were analyzed by CE with optimum conditions phosphate running buffer (pH 2.0), applied voltage of 20kV and 25°C. Under the optimum conditions, limits of detection (LOD) and quantification (LOQ) for GLP and MAT and ETH and DMT were 2.31-2.68-2.48-2-91 and 7.72-8.91-8.43-7.95ng/ mL⁻¹ respectively. Preconcentration factor and RSD for five replicates of each organophosphorus were calculated to be 200 and 4.06-3.93-4.32-3.65 respectively.

esad14274@gmail.com