

Land leveling using GIS, genetic and pso (particle swarm optimization) algorithms by Optimization of energy consumption – Alzoubi Ilesham -University of Tehran

Alzoubi Ilesham

Department of Pharmacy, College of Medical Sciences, University of Tehran, Iran

One of the most important steps to prepare soil is land leveling. Land leveling with machines requires considerable energy. To increase the accuracy of the calculations, the point height collected from mapping (50 m × 50 m) is inserted into the GIS environment. The rest of the unknown coordinates were obtained using interpolation and a triangular network model (TIN) was used to determine the exact volume of earthworks. In all methods, the equation of the leveling plate, excavation and embankment volumes and maps of land surface after leveling, separation of excavation and embankment and the energy consumption including power of the machine, fuel and manpower were calculated. Then different methods were compared. The results showed that the ratio of excavation to embankment based on the methods of minimum least squares, genetic algorithm, linear algorithm for optimizing of the particle motions, the particle motion curve algorithm are equal to 1.26, 1.14, 1.12, and 1.16, respectively. On the other hand, the results showed that the method of the particle motion curve algorithm has been shown a 45% reduction in energy consumption in the leveling operation relative to the method of minimum least squares. The genetic algorithm can reduce energy consumption by 42 percent. Between the models used in the method of genetic algorithm, model No. 1 has been estimated that the largest portion of energy consumption is relevant to the fuel (up to 71.83 percent) and the lowest portion of energy consumption is relevant to the manpower (up to 0.38 percent). Therefore, the present study recommends the model of plate-curve genetic algorithm as the best model. Vitality productive structures' issue coordinated into the region and CO₂ outflow decrease techniques and approaches is one of the principle worries in the European Union (EU). So as to accomplish a viable effect, rather than simply focusing on the improvement regarding vitality productivity to one specific structure, this methodology expects difficulties to be tackled in a whole region or a whole region. As needs be, it is critical understanding the exhaustive private structure stock models in the urban condition ready to advance an economical vitality arranging.

In this paper we portray another philosophy dependent on two diverse displaying approaches top-down and base up with the intend to assess the structures vitality utilization model of a district. This technique is for the most part dependent on data that is as of now accessible on building stock from the writing and information assortment (i.e., specialized branch of region, web, vitality inspectors and others) which is later moved into the Geographic data framework (GIS). Into this in future investigations GIS stage gives the data on vitality execution in the entire city just as making the urban vitality maps for evaluating retrofitting situations and bolster dynamic for approach usage to accomplish feasible urban arranging. This investigation is a piece of a progressing Smart City examine study, national bunch venture named Zero Energy Buildings in Smart Urban Districts (EEB) and is tried in a medium measured town in the Piedmont locale (Italy), and the outcomes are talked about. The particular vitality use for space warming and boiling water creation as capacity of the structure development period and the surface to volume proportion S/V for private structures for Settimo Torinese. The particular vitality use for space warming and heated water creation as capacity of the structure development period and the surface to volume proportion S/V for private structures for Settimo Torinese. GIS-Based Energy Consumption Model at the Urban Scale for the Building Stock Sara Torabi Moghadam¹, Guglielmina Mutani², Patrizia Lombardi¹ ¹ Interuniversity Department of Regional and Urban Studies and Planning, Politecnico di Torino, ² Department of Energy, Politecnico di Torino Abstract Energy effective structures' issue coordinated into the area and CO₂ outflow decrease methodologies and approaches is one of the primary worries in the European Union (EU). So as to accomplish a successful effect, rather than simply focusing on the improvement as far as vitality effectiveness to one specific structure, this methodology expects difficulties to be fathomed in a whole region or a whole region.