OPEN ACCESS Freely available online

Journal of Physical Chemistry & Biophysics

Perspective

Quantitative Analysis of Nanomechanical Properties Using Atomic Force Microscopy

Marc Sobolev*

Department of Physics, Graz University, Graz, Austria

INTRODUCTION

Atomic Force Microscopy (AFM) has become an indispensable tool for measuring the mechanical properties of materials at the nanoscale. AFM allows scientists to directly observe and quantify the mechanical response of surfaces with high spatial resolution, making it an essential technique in various fields, including materials science, biology, and nanotechnology. Through its ability to measure forces as small as piconewtons, AFM provides valuable insights into the mechanical properties of soft and hard materials, enabling the development of new materials and therapies.

DESCRIPTION

Principle of atomic force microscopy

- AFM operates by scanning a sharp tip over a surface while measuring the interaction between the tip and the surface.
- The AFM probe typically consists of a cantilever with a sharp tip at its end. As the tip approaches the surface, the cantilever bends in response to the forces between the tip and the surface. This bending is detected by a laser beam reflected off the cantilever into a position-sensitive detector.
- The deflection of the cantilever is then converted into a force measurement, which provides information about the local mechanical properties of the surface at the nanoscale.

Methods of nanomechanical property measurement

AFM can be used to measure several nanomechanical properties, including elasticity, stiffness, adhesion, hardness and friction. Different techniques within AFM are employed to quantify these properties, depending on the type of material and the desired measurement.

Force spectroscopy: One of the most common methods for studying nanomechanical properties with AFM is force spectroscopy. In this technique, the AFM tip is brought into contact with the surface, and a series of force-distance curves are recorded. The force exerted by the tip on the surface is plotted as a function of the distance between the tip and the surface. From the shape of the force curve, quantitative information about the material's mechanical properties can be extracted.

For example, the stiffness of a material can be determined by analyzing the slope of the retraction portion of the force curve. The slope represents the stiffness of the surface at the point of contact, providing insights into the elasticity of the material.

Mapping elasticity and stiffness: In addition to force spectroscopy, AFM can be used to map the spatial variation of mechanical properties across a surface. In a technique called nanoindentation, the AFM tip is pressed into the surface, and the resulting indentation depth is measured as a function of applied force. By analyzing the indentation data, the local stiffness and elasticity of the material can be mapped with high spatial resolution.

Elastic modulus maps are particularly useful for studying heterogeneous materials, such as biological tissues or composite materials, where different regions may exhibit distinct mechanical properties. This capability is crucial for applications in biomedical research, where understanding the mechanical properties of tissues can aid in the design of medical devices or the evaluation of disease states.

Dynamic force spectroscopy: Dynamic force spectroscopy is another AFM-based method that focuses on the time-dependent response of a material to applied forces. In this technique, the AFM tip oscillates above the surface, and the interaction forces between the tip and the material are measured as a function of the frequency and amplitude of the oscillation. This provides information about the viscoelastic properties of the material, including its ability to dissipate energy.

Dynamic force spectroscopy can be particularly useful for characterizing soft materials, such as polymers and biological tissues, which exhibit both elastic and viscous behaviors. The ability to quantify both elastic and viscous components of the material's response offers a more complete understanding of its mechanical properties.

Correspondence to: Marc Sobolev, Department of Physics, Graz University, Graz, Austria; E-mail: Sobolev_marc@hotmail.com

Received: 06-Jan-2025, Manuscript No. JPCB-25-36737; **Editor assigned:** 09-Jan-2025, PreQC No. JPCB-25-36737 (PQ); **Reviewed:** 23-Jan-2025, QC No. JPCB-25-36737; **Revised:** 18-Feb-2026, Manuscript No. JPCB-25-36737 (R); **Published:** 25-Feb-2026, DOI: 10.35841/2161-0398.26.16.449

Citation: Sobolev M (2026) Quantitative Analysis of Nanomechanical Properties Using Atomic Force Microscopy. J Phys Chem Biophys. 16:449.

Copyright: © 2026 Sobolev M. This is an open-access article distributed under the terms of the Creative Commons Attribution License, which permits unrestricted use, distribution, and reproduction in any medium, provided the original author and source are credited.

Applications of AFM in nanomechanical analysis

Here are some notable applications of AFM in nanomechanical analysis:

Material science and nanotechnology: In materials science, AFM plays a significant role in the characterization of nanostructured materials, thin films, and coatings. By measuring the nanomechanical properties of these materials, researchers can assess their performance and suitability for various applications, such as microelectronics, coatings, and sensors.

AFM is also used to study the mechanical properties of nanocomposites and nanostructures, which have become increasingly important in the development of advanced materials.

Biological and biomedical research: In the field of biology, AFM has become an important tool for studying the mechanical properties of cells, tissues, and biomolecules. The stiffness of cells, for instance, has been shown to correlate with their state of differentiation, migration, or disease progression. AFM is widely used in cell mechanics studies to measure cellular elasticity and to assess how cells respond to changes in their environment, such as during cancer progression or tissue regeneration.

In addition to cellular studies, AFM is used to investigate the mechanical properties of biomolecules, such as proteins, DNA, and lipids. Force spectroscopy can reveal how these molecules interact with other molecules or surfaces, providing insights into processes like protein folding, receptor-ligand binding, and drug delivery.

Surface characterization and coating technologies: AFM is frequently used in the characterization of coatings and surface treatments. For example, the adhesion strength of coatings can be measured by probing the interaction forces between the AFM tip and the coating surface.

Similarly, the hardness and elasticity of materials used in manufacturing, such as metals, ceramics, and polymers, can be quantified using AFM. This helps manufacturers optimize material selection and design, ensuring the longevity and reliability of products.

CONCLUSION

Atomic force microscopy has proven to be an essential tool for the quantitative analysis of nanomechanical properties, offering valuable insights into the mechanical characteristics of a wide range of materials. From material science to biomedical research, AFM enables researchers to measure stiffness, elasticity, adhesion and other critical properties with high spatial resolution. As the technique continues to advance, its ability to probe the mechanical properties of materials at the nanoscale will further enhance our understanding of material behavior and open new avenues for innovation in various fields.