

How does biodiesel compare to other renewable diesel fuels

Michael D Eggleston

International Engineering Student, Pharmaceutical Chemical Engineering, Germany

ABSTRACT

Focusing on heavy modes of transport, diesel fuel currently provides the majority of the kick that is needed to meet the demands of the modern standard of living in the developed world and the increasing demand of energy in the developing world. Recently, diesel is facing a backlash after Volkswagen's diesel-gate, which revealed the intentional manipulation of nitrogen oxides (NO_x) in official engine tests. The scandal hit at a time when air pollution is becoming an increasingly political issue for cities around the world. As air and sea traffic grow and as the developing world expands economically, the diesel engine will continue to play a key role in the transportation sector. Therefore, de-fossilizing this area of the transportation sector for the long-term will be necessary if the world's governments are to meet temperature reduction targets set by the Paris Climate Agreement, as well as reduce the impact of anthropogenic climate change. Although alternative, renewable fuels, also referred to as biofuels, for diesel engines can be derived from a wide range of bio-based feedstocks, their methods of production, vehicle use and benefits are distinctly different from each other. The purpose of this presentation is to provide an informative background to renewable fuels available for the diesel engine in order to inform key decision makers and people who are just curious to learn more about the role alternative diesel fuels will play in the near future.

OPINION

Focusing on heavy modes of transport such as trucks, trains, boats and barges, diesel fuel currently provides the majority of the "kick" that is needed to meet the demands of the modern standard of living in the developed world and the increasing demand of energy in the developing world.

Recently, diesel is facing a "backlash" after Volkswagen's "dieselgate", which revealed the intentional manipulation of nitrogen oxides (NO_x) in official engine test results. The scandal hit at a time when air pollution was becoming an increasingly political issue for cities around the world. Some cities, including Paris, Mexico City and Madrid, have even announced bans for diesel vehicles from 2019 onwards.

As air and sea traffic grow and as the developing world expands economically, the diesel engine will continue to play a key role in the transportation sector. Therefore, "defossilizing" this area of the transportation sector for the long-term will be necessary if the world's governments are to meet temperature reduction targets set by the Paris Climate Agreement.

Although alternative, renewable fuels, also referred to as Biofuels, for diesel engines can be derived from a wide range of bio-based feedstock's, their methods of production, vehicle use and benefits are distinctly different from each other.

The purpose of this presentation is to provide a general overview of the renewable fuels available for the diesel engine in order to inform key decision makers and people who are just curious to learn more about the role alternative diesel fuels will play in the near future. Included among the various alternative diesel fuel options that will be discussed are biodiesel (FAME), hydrogenated vegetable oil (HVO), Gas-to-Liquid (GtL) and Biomass-to-Liquid (BtL) fuels.

Whenever renewable fuels are discussed they should always be able to answer the following question...

- a. Is it coherent as it claims to be?
- b. Is it co-producible?
- c. Is it compatible with the diesel engine?
- d. How competitive is it with petrol-diesel?

The first section is addressed to how sustainable renewable diesel fuels are, or in other words, how coherent is the fuel? This breaks down into what feedstock the fuel is made from and the emissions it emits into the atmosphere when combusted. For all intents and purposes, this presentation just focuses only on comparing the greenhouse gas (GHG) emissions of the fuels, primarily carbon dioxide (CO₂), carbon monoxide (CO), nitrous oxides (NO_x), hydrocarbons (HC) and particulate matter (PM). On the surface FAME provides the majority of secondary GHG emission reductions, such as that in PM, CO and HC. However, with conventional feedstock's, CO₂ emissions of FAME remain below newly proposed legislation in the EU (Renewable Energy Directive – RED II) and also pose a serious risk to increase NO_x emissions. On the other hand HVO and BtL provide significant CO₂ reductions and GtL proves to be a suitable long-term substitute to FAME in regards to HC reductions, as long as it is accompanied with a particle filter to compensate for reduced PM reductions.

Moving towards the production of renewable diesel fuels, HVO is the only "drop-in" fuel to which can be manufactured with the same existing petrol-diesel infrastructure operating at similar conditions such as temperature and process chemistry (hydrodesulphurization). The processes of the other fuels take on other forms such as the exchange of alcohols (FAME), the synthesis of syngas (GtL) and the intense break down of hydrocarbons via pyrolysis (BtL).

DISCUSSION

Discussing whether these fuels are compatible with the diesel engine requires an understanding of the limitations and advantages these fuels propose. For example, in most cases there is a strict blending limit to about 20% for biodiesel (B20) to prevent increased NO_x emissions, decreased torque and corrosion of engine parts such as gaskets. Biodiesel is not all that bad having superior lubricity and handling (flash point) properties. Ultimately, if the aim is to reduced emissions such

as sulfur, particulate matter etc (expect for NO_x) it is best to have a higher level blend, such as B20, however if the aim is to increase lubricity in ultra -low sulfur diesel (ULSD), for example, then blends of 2-5% (B2-B5) will suffice. In comparison to other renewable diesel fuels, biodiesel is outmatched by ignitability (cetane number), energy density (besides that of GtL) and its storage performance (oxidative stability). Lastly, in reviewing how competitive biodiesel is in comparison to other developing and available renewable diesel fuels, understanding the results previously mentioned in terms of the short to long-term integration is key. Therefore I propose, that:

- i. FAME from conventional feedstock's should only serve as an additive to improve lubricity, storage handling and decrease PM emissions in the short-term as Biological-GTL (FAME produced from syngas) develops
- ii. HVO should serve as an immediate drop-fuel fuel with immediate CO₂ reductions in the short to medium-term
- iii. Immediate attention is needed to coordinate a decentralized collection of waste residues to make GtL/BtL cost competitive
- iv. Conduct research into GtL/BtL co-blending for the long-term.

CONCLUSIONS AND OUTLOOK

As the above conversation shows, the issue of biodiesel and sustainable diesel is unpredictable. Both biodiesel and sustainable diesel have focal points regarding carbon sustainability contrasted with petro diesel however there are preferences and impediments to either in terms of fuel properties, ecological issues and vitality balance. There is just a constrained measure of feedstock accessible to fulfil possible interest for the two fills. In spite of all endeavours to create extra feedstocks, this will probably stay an issue later on. In this manner, a noteworthy inquiry seems, by all accounts, to be if biodiesel and inexhaustible diesel contend with or supplement one another. Either fuel can just supplant a couple of percent of the petro diesel advertise. A conceivable angle is if the utilization of these powers ought to be gathered in territories where the most advantage is gotten from either. If there should be an occurrence of biodiesel, this would be exploiting ecological advantages and if there should arise an occurrence of sustainable diesel this would be exploiting of improved virus stream properties predominantly for flying purposes, given the inexhaustible diesel is of the sort to a great extent made out of littler and isomerized molecules. While this effect may not be fully clear, an issue with potential impact could be production scale, i.e., would more biodiesel or more renewable diesel be produced.